

KC 0611 Roofbolter

Low Profile

Features

- **Compact**

The KC 0611 Roofbolter sits only 1.97 feet tall and extends to 3.61 feet.

- **Light weight**

The KC 0611 weighs only 70 lbs.

- **Inverted leg**

The inverted leg design ensures there are no moving parts on the floor, prolonging leg and seal life.

- **Power Pack Motor**

The Power Pack Motor is dependable, light, compact and can be fully detached in minutes.

- **Advanced Dumping**

The Superdump system can save valuable time in stressed strata conditions. The twin dump valves dump at twice the speed of an other roofbolter.

- **Low Maintenance**

The KC 0611 is extremely reliable and is virtually maintenance free (under normal working conditions).



*MPI Recommends using
Brady Rock Drill Oil
for all Applications of the
KC 0611 Roofbolter*



Technical Specifications

KC 0611 Roofbolter

Closed Height	1.97 feet
Extended Height	3.61 feet
Operating Pressure	100 psi
Air Consumption	120 cfm
Output	150 ft lbs @ stall
Torque Available Through Cluth	250 ft lbs
HIGH TORQUE MODEL	
Max. Leg Thrust (1st stage)	2,500 ft lbs
Max. Leg Thrust (2nd stage)	2,000 ft lbs
Max. Leg Thrust (3rd stage)	1,500 ft lbs
Approximate Weight	70 lbs
Noise Level	94 dBA

Dry Head

Compatible with MPI's Dust Collection Unit



Wet Head

Designed to minimize dusty working conditions

