

KC 0821 Roofbolter

Features

- **Lightweight**
95 lbs
- **Compact**
The compact design has been developed for easy operation.
- **Inverted Leg**
This design is the break-through of the century in telescopic air legs. No moving parts at floor level guarantees longer leg and seal life.
- **Advanced Thrust**
Designed for easy cable bolting.
- **Power Pack Motor**
This motor is light, compact, and can easily be detached in minutes.
- **Advanced Dumping**
Rambors advanced Superdump system saves time in stressed strata conditions.
- **Low Maintenance**
The King Cobra Roofbolter is designed for easy dismantling and assembly keeping maintenance costs low.





KC 0821 Roofbolter
25 Allegheny Square
Glassport, PA 15045
(412) 664-7788
Fax (412) 664-7717

1114 Sixteen Road
Fruita, CO 81521-2029
(970) 858-0600
Fax (970) 858-0696

Technical Specifications

KC 0821

Closed Height	2.7 feet
Extended Height	6.9 feet
Operating Pressure	100 psi
Air Consumption	120 cfm
Output	118 lbf @ stall
Torque Available Through Clutch	250 lbf
4 STAGE MODEL	
Max. Leg Thrust (1st stage)	2,000 lbf
Max. Leg Thrust (2nd stage)	1,500 lbf
Max. Leg Thrust (3rd stage)	1,000 lbf
Approximate Weight	95 lbs
Noise Level	94 dBA

Dry Head (Dust Collection Head)

Compatible with MPI's Dust Collection Unit



Wet Head

Designed to minimize dusty working conditions

